## LLLEvo12<sup>™</sup>

The most affordable, compact and simple vertical form, fill and seal machine available on the market.

- Stainless steel construction allows for packaging pet food, frozen food, vegetables, snacks, granular products, cereals and other food related applications.
- Easily interfaced with automatic filling equipment from partners like;
  All Fill, Yamato, and Weigh Right.



### STANDARD HAWK V12 FEATURES

- Off the shelf parts
- High speed stepper powered jaw and pull-down belts
- · Self centering film drive system
- Will accept rolls up to 20" in diameter and web widths up to 25.25" wide
- Allen Bradley MicroLogix 1400 PLC Control System
- No tool change over from the roll through the forming tube
- Photo eye for registered film
- Encoder for clear film
- Will integrate with scales, augers, cup fillers and other infeed devices
- Will run a wide variety of films

**BENEFITS** 

- · Easy to Operate
- Easy to Maintain
- Quick bag size change over
- · Best value per square foot in the industry
- Reduces labor and material cost



PACKAGING

# LLL Evo12™

### **HAWK EVO12 OPTIONS**

- Gusseting
- Flat bottomed bags
- · Gas flushing
- · Hole punches
- Printers
- Exit conveyors
- Tear notch
- · Poly sealing system
- · Load shelf
- Stripper
- Poker
- Bag tapper
- · Bag shaker
- Wash down construction
- · Other options available upon request

### HAWK EVO12 FILM PERFORMANCE CRITERIA

COF

High Integrity Seal

Tear Notch for Easy Opening

Peelable

Anti-Static

Anti-Skid

Anti-Corrosive

### **BARRIER PROPERTIES**

**MVTR-** Moisture Specifications

OTR- Oxygen Specifications

**Grease Barriers** 

Water Barriers

## TECHNICAL SPECIFICATIONS

Speed Up to 140 Empty Bags per Minute

Bag Widths 2 to 12 inches

Bag Lengths 2" to 16" standard; 18" Vertical Seal Bar is Optional

Bag Materials Laminated & Polyethylene

Electrical 220 VAC 60Hz, 15 AMPS single phase

Air 60 PSI, 2 to 3 CFM



PACKAGING

888-922-1622

WWW.IPACK.COM